



Epic Nylon Mesh

Wilflex™ Epic Nylon Mesh Base is a non-phthalate ink designed to print directly onto 100% Nylon open mesh and dazzle cloth. Epic Nylon Mesh Base can be used with Epic PCs or EQs to produce highly durable graphics.

- 11422PFXMESH EPIC NYLON MESH BASE
- 11000PFXMESH EPIC NYLON MESH WHITE
- 19000PFXMESH EPIC NYLON MESH BLACK

HIGHLIGHTS

- High gloss finish
- Excellent durability
- Excellent adhesion to fabrics

PRINTING TIPS

- Epic Nylon Mesh Base will not adhere to nylon jackets or water-repellent fabrics without the addition of ASI Hugger Catalyst. If the material has been treated to repel water, the waterproofing must be removed and the addition of the ASI Hugger Catalyst at 10% by weight will be necessary. Wipe down the print area with rubbing alcohol or acetone if printing on a tightly woven material.

COMPLIANCE

- Non-phthalate
- For individual compliance certifications and conformity statements, please visit: www.avient.com/wilflex-compliance

PRECAUTIONS

The information above is given in good faith and does not release you from testing inks and fabrics to confirm suitability of substrate and application process to meet your customer standards and specifications




AVIENT
SPECIALTY
INKS

V1.31 (Modified: 08/01/2022)

PRODUCT INFORMATION BULLETIN



RECOMMENDED PARAMETERS



Fabric Types

Untreated 100% nylon mesh, dazzle cloth



Mesh

Count : 61-196 t/in (24-77 t/cm)
Tension: 25-35 n/cm2



Squeegee

Durometer: 60-90
Profile: Straight
Stroke: Medium stroke
Angle:



Stencil

2 over 2
Off Contact: 1/16" (2mm)
Emulsion Over Mesh:



Flash & Cure

Flash: 160°F (70°C)
Cure: 300°F (150°C)



Pigment Loading

NA



Wilflex™ Additives

ASI Viscosity Buster - 3% max



Storage

65-90°F (18-32°C)
Avoid direct sunlight
Use within one year of receipt



Clean Up

Ink degradant or press wash



Health & Safety

Find SDS information here:
www.avient.com/resources/safety-data-sheets
or contact your local CSR

2022, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.