





Wilflex™ Epic™ Transflex™ Inks

Wilflex™ Epic™ Transflex™ Inks are high-performance plastisol transfer inks that produce exceptionally soft and durable prints. They provide excellent on-press performance and versatile printing options, offering top-quality results with every application.

PRODUCT HIGHLIGHTS

- High-speed wet-on-wet printing
- · Ideal soft hand with great wash fastness
- Options for opaque and translucent colors
- · Hot-split, hot-peel, and cold-peel capabilities
- Suitable for uncoated and coated release papers
- Compatible with print solid color and halftone graphics

BENEFITS

- Save Time Mix colors quickly and accurately while using standard printing procedures
- Avoid Waste Wilflex Epic Inks do not dry in the screen or bucket and can be further used with a color mixing system
- Improve Productivity High-speed production allows printers to start and stop as needed without cleaning screens

COMPLIANCE

Certified to ECO PASSPORT by OEKO-TEX[®]

PRODUCTS

Category	Code	Product Name
Blacks	19000TFX	Epic TFX Soft Black
Bases	K2305	Epic Transflex Base
Clears	10007TFX	Epic TFX Transclear
Specialty Inks	10211TFX	Epic TFX Printable Adhesive
	10290PFXSA	Epic Superbond Adhesive
Texture Bases	10480TFXPUFF	Epic Transfer Puff Base
Whites	11000TFX	Epic TFX Super White
	11010TFX	Epic TFX Premium White
	11620TFX	Epic TFX Lithoprint White

1.844.4AVIENT www.avient.com



Copyright © 2024, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES OR MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.