

## **Zodiac<sup>™</sup> Aquarius<sup>™</sup> Water-Based Digital Max White**

Zodiac<sup>™</sup> Aquarius<sup>™</sup> Water-Based Digital Max White is developed to produce a smooth, receptive screen printed under base for digital inks. Digital hybrid ink printers can achieve brilliant color yield, high-definition prints with soft, flexible hand, and excellent wash performance.

Zodiac Aquarius Digital Max White does not require a top coat to achieve excellent wash durability, making it an innovative way to increase screen printing productivity.

### **KEY CHARACTERISTICS**

- Provides soft, flexible hand
- Fast cure time (90 seconds)
- Receptive to digital hybrid inks
- Maintains print definition
- Matte finish
- Upholds excellent wash durability without a top coat
- Compatible with Aquarius Migration Stop for printing on 100% polyester fabrics



## ZODIAC AQUARIUS DIGITAL MAX WHITE

Cure Conditions  
325°F/165°C for 90s or 01:30

100% Polyester

### \* EQUIPMENT USED



Flash Cure Unit








HotHead™ Fabric  
Compression System



DS-4000 Digital™ Squeegee®  
Hybrid Printing System



SPRINT® 3000 Gas Conveyor Dryer

P	Product Used	+*	Mesh	Duro	Ang	Stk	Pres	Spd	OC	Flash Temp
1	Aquarius Migration Stop		110 t/in / 43 t/cm	60/90/60	15	2	45	4	1&1	
2	**Flash**									230°F/110°C
3	M&R HotHead™									
4	Aquarius White HS		195t/in / 77t/cm	60/90/60	15	2	35	4	1&1	
5	**Flash**									230°F/110°C
6	Aquarius Digital Max White		195t/in / 77t/cm	60/90/60	15	2	50	4	1&1	
7	M&R® Digital Squeegee									
8	**Flash**									230°F/110°C

[www.zodiacinks.com](http://www.zodiacinks.com)



Copyright © 2024, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.